

BARCODE SINGLE LASER SCANNER TARGETING**BACKGROUND OF THE INVENTION**

5

1. Field of the Invention:

The present invention relates generally to an apparatus for calibrating an apparatus for retrieving objects from an array of storage cells.

10

2. Background of the Invention:

Storage library systems are capable of storing and rapidly retrieving large quantities of information stored on storage media cartridges. Such storage library systems often use robotic mechanisms to improve the speed of information retrieval and the reliability of maintaining the storage library cartridge inventory. These robotic mechanisms typically comprise a hand mechanism positioned on a movable arm. To retrieve information, the robotic arm is moved to position the hand near the inventory location of a desired media cartridge. The hand is then activated to grip the desired cartridge and remove it from the library inventory location. The robotic arm with the hand gripping the cartridge then moves to an appropriate position to further process the cartridge. In this manner, the robotic hand manipulates the cartridge for access to information stored on the cartridge.

However, in order to grip the cartridge, the position of the robotic arm with respect to the cartridge

Docket No. 2001-067-TAP

within the library must be determined. Positional accuracy of the robotic arm and any devices attached thereto affects both the repeatability of an operation as well as the ability of the robotic arm to accurately perform the particular task required of it. There are many different arm calibration arrangements known in the art, and many of these entail the use of some sort of sensor to determine the position of the robotic arm.

A common method of calibrating the position of the robotic arm gripper mechanism is to use a vision system to orient the robotic arm with respect to one or more baseline targets located in the work space. Often these vision systems are located underneath or above the robotic arm and are oriented at an angle relative to the robotic arm. These vision systems are located at an angle so that a target on the work space can be imaged, and then a target located on a part of the robotic arm that is extended into the field of view of the vision system is imaged. The two images are compared and the position of the robotic arm is adjusted such that the target on the robotic arm is aligned with the target on the work piece when extended.

However, orienting the vision system at an angle causes the inclusion of the vision system with the robotic arm to take up a large amount of space. Thus, a significant portion of the space within the storage library system is unusable for placing storage cells. This is due to the fact that if, for example, the vision system is located below the robotic arm, an amount of space equal to the height or thickness of the angled

Docket No. 2001-067-TAP

vision system at the bottom of the storage retrieval system cannot be accessed by the robotic arm since the vision system comes into contact with the floor of the storage library system before the robotic arm. Thus, the robotic arm is prevented from going low enough within the storage library system to engage and retrieve an object stored in a storage cell located within the thickness of the angled vision system from the floor of the storage library system.

b6
b7C
b7D
b7E
b7F
b7G
b7H
b7I
b7J
b7K
b7L
b7M
b7N
b7O
b7P
b7Q
b7R
b7S
b7T
b7U
b7V
b7W
b7X
b7Y
b7Z
b7AA
b7AB
b7AC
b7AD
b7AE
b7AF
b7AG
b7AH
b7AI
b7AJ
b7AK
b7AL
b7AM
b7AN
b7AO
b7AP
b7AQ
b7AR
b7AS
b7AT
b7AU
b7AV
b7AW
b7AX
b7AY
b7AZ
b7BA
b7BB
b7BC
b7BD
b7BE
b7BF
b7BG
b7BH
b7BI
b7BJ
b7BK
b7BL
b7BM
b7BN
b7BO
b7BP
b7BQ
b7BR
b7BS
b7BT
b7BU
b7BV
b7BW
b7BX
b7BY
b7BZ
b7CA
b7CB
b7CC
b7CD
b7CE
b7CF
b7CG
b7CH
b7CI
b7CJ
b7CK
b7CL
b7CM
b7CN
b7CO
b7CP
b7CQ
b7CR
b7CS
b7CT
b7CU
b7CV
b7CW
b7CX
b7CY
b7CZ
b7DA
b7DB
b7DC
b7DD
b7DE
b7DF
b7DG
b7DH
b7DI
b7DJ
b7DK
b7DL
b7DM
b7DN
b7DO
b7DP
b7DQ
b7DR
b7DS
b7DT
b7DU
b7DV
b7DW
b7DX
b7DY
b7DZ
b7EA
b7EB
b7EC
b7ED
b7EE
b7EF
b7EG
b7EH
b7EI
b7EJ
b7EK
b7EL
b7EM
b7EN
b7EO
b7EP
b7EQ
b7ER
b7ES
b7ET
b7EU
b7EV
b7EW
b7EX
b7EY
b7EZ
b7FA
b7FB
b7FC
b7FD
b7FE
b7FF
b7FG
b7FH
b7FI
b7FJ
b7FK
b7FL
b7FM
b7FN
b7FO
b7FP
b7FQ
b7FR
b7FS
b7FT
b7FU
b7FV
b7FW
b7FX
b7FY
b7FZ
b7GA
b7GB
b7GC
b7GD
b7GE
b7GF
b7GG
b7GH
b7GI
b7GJ
b7GK
b7GL
b7GM
b7GN
b7GO
b7GP
b7GQ
b7GR
b7GS
b7GT
b7GU
b7GV
b7GW
b7GX
b7GY
b7GZ
b7HA
b7HB
b7HC
b7HD
b7HE
b7HF
b7HG
b7HH
b7HI
b7HJ
b7HK
b7HL
b7HM
b7HN
b7HO
b7HP
b7HQ
b7HR
b7HS
b7HT
b7HU
b7HV
b7HW
b7HX
b7HY
b7HZ
b7IA
b7IB
b7IC
b7ID
b7IE
b7IF
b7IG
b7IH
b7II
b7IJ
b7IK
b7IL
b7IM
b7IN
b7IO
b7IP
b7IQ
b7IR
b7IS
b7IT
b7IU
b7IV
b7IW
b7IX
b7IY
b7IZ
b7JA
b7JB
b7JC
b7JD
b7JE
b7JF
b7JG
b7JH
b7JI
b7JJ
b7JK
b7JL
b7JM
b7JN
b7JO
b7JP
b7JQ
b7JR
b7JS
b7JT
b7JU
b7JV
b7JW
b7JX
b7JY
b7JZ
b7KA
b7KB
b7KC
b7KD
b7KE
b7KF
b7KG
b7KH
b7KI
b7KJ
b7KK
b7KL
b7KM
b7KN
b7KO
b7KP
b7KQ
b7KR
b7KS
b7KT
b7KU
b7KV
b7KW
b7KX
b7KY
b7KZ
b7LA
b7LB
b7LC
b7LD
b7LE
b7LF
b7LG
b7LH
b7LI
b7LJ
b7LK
b7LL
b7LM
b7LN
b7LO
b7LP
b7LQ
b7LR
b7LS
b7LT
b7LU
b7LV
b7LW
b7LX
b7LY
b7LZ
b7MA
b7MB
b7MC
b7MD
b7ME
b7MF
b7MG
b7MH
b7MI
b7MJ
b7MK
b7ML
b7MM
b7MN
b7MO
b7MP
b7MQ
b7MR
b7MS
b7MT
b7MU
b7MV
b7MW
b7MX
b7MY
b7MZ
b7NA
b7NB
b7NC
b7ND
b7NE
b7NF
b7NG
b7NH
b7NI
b7NJ
b7NK
b7NL
b7NM
b7NN
b7NO
b7NP
b7NQ
b7NR
b7NS
b7NT
b7NU
b7NV
b7NW
b7NX
b7NY
b7NZ
b7OA
b7OB
b7OC
b7OD
b7OE
b7OF
b7OG
b7OH
b7OI
b7OJ
b7OK
b7OL
b7OM
b7ON
b7OO
b7OP
b7OQ
b7OR
b7OS
b7OT
b7OU
b7OV
b7OW
b7OX
b7OY
b7OZ
b7PA
b7PB
b7PC
b7PD
b7PE
b7PF
b7PG
b7PH
b7PI
b7PJ
b7PK
b7PL
b7PM
b7PN
b7PO
b7PP
b7PQ
b7PR
b7PS
b7PT
b7PU
b7PV
b7PW
b7PX
b7PY
b7PZ
b7QA
b7QB
b7QC
b7QD
b7QE
b7QF
b7QG
b7QH
b7QI
b7QJ
b7QK
b7QL
b7QM
b7QN
b7QO
b7QP
b7QQ
b7QR
b7QS
b7QT
b7QU
b7QV
b7QW
b7QX
b7QY
b7QZ
b7RA
b7RB
b7RC
b7RD
b7RE
b7RF
b7RG
b7RH
b7RI
b7RJ
b7RK
b7RL
b7RM
b7RN
b7RO
b7RP
b7RQ
b7RR
b7RS
b7RT
b7RU
b7RV
b7RW
b7RX
b7RY
b7RZ
b7SA
b7SB
b7SC
b7SD
b7SE
b7SF
b7SG
b7SH
b7SI
b7SJ
b7SK
b7SL
b7SM
b7SN
b7SO
b7SP
b7SQ
b7SR
b7SS
b7ST
b7SU
b7SV
b7SW
b7SX
b7SY
b7SZ
b7TA
b7TB
b7TC
b7TD
b7TE
b7TF
b7TG
b7TH
b7TI
b7TJ
b7TK
b7TL
b7TM
b7TN
b7TO
b7TP
b7TQ
b7TR
b7TS
b7TT
b7TU
b7TV
b7TW
b7TX
b7TY
b7TZ
b7UA
b7UB
b7UC
b7UD
b7UE
b7UF
b7UG
b7UH
b7UI
b7UJ
b7UK
b7UL
b7UM
b7UN
b7UO
b7UP
b7UQ
b7UR
b7US
b7UT
b7UU
b7UV
b7UW
b7UX
b7UY
b7UZ
b7VA
b7VB
b7VC
b7VD
b7VE
b7VF
b7VG
b7VH
b7VI
b7VJ
b7VK
b7VL
b7VM
b7VN
b7VO
b7VP
b7VQ
b7VR
b7VS
b7VT
b7VU
b7VV
b7VW
b7VX
b7VY
b7VZ
b7WA
b7WB
b7WC
b7WD
b7WE
b7WF
b7WG
b7WH
b7WI
b7WJ
b7WK
b7WL
b7WM
b7WN
b7WO
b7WP
b7WQ
b7WR
b7WS
b7WT
b7WU
b7WV
b7WW
b7WX
b7WY
b7WZ
b7XA
b7XB
b7XC
b7XD
b7XE
b7XF
b7XG
b7XH
b7XI
b7XJ
b7XK
b7XL
b7XM
b7XN
b7XO
b7XP
b7XQ
b7XR
b7XS
b7XT
b7XU
b7XV
b7XW
b7XX
b7XY
b7XZ
b7YA
b7YB
b7YC
b7YD
b7YE
b7YF
b7YG
b7YH
b7YI
b7YJ
b7YK
b7YL
b7YM
b7YN
b7YO
b7YP
b7YQ
b7YR
b7YS
b7YT
b7YU
b7YV
b7YW
b7YX
b7YY
b7YZ
b7ZA
b7ZB
b7ZC
b7ZD
b7ZE
b7ZF
b7ZG
b7ZH
b7ZI
b7ZJ
b7ZK
b7ZL
b7ZM
b7ZN
b7ZO
b7ZP
b7ZQ
b7ZR
b7ZS
b7ZT
b7ZU
b7ZV
b7ZW
b7ZX
b7ZY
b7ZZ

10 However, as the need to store more and more data increases and the price paid for space also increases, the amount of money necessary to store data is increased. Thus, the wasted space within a library storage system becomes more and more intolerable. Therefore, there is a
15 need for a calibration system that requires less space than current systems and that allows for a denser concentration of storage cells within a storage library system.

Docket No. 2001-067-TAP

SUMMARY OF THE INVENTION

The present invention provides a robot apparatus and a barcode scanner to be used for collecting positional data parallel to the scan direction in, for example, a library storage system. In one embodiment, the robotic apparatus includes a barcode scanner with a scan path and an attenuation surface within the scanner scan path. The barcode scanner scans the target while the robotic apparatus is moved in a direction parallel with the scan path. Positional data is collected in conjunction with the readability limits of the barcode target. The central position of the target in a parallel direction to the scan path is determined based on the readability of the barcode target and the correlating positional data. The barcode scanner can also scan the target while the robotic apparatus is moved in a direction perpendicular with the scan path. Positional data is collected in conjunction with the readability limits of the barcode target. The central position of the target in a perpendicular direction to the scan path is determined based on the readability of the barcode scanner and the correlating positional data.

Docket No. 2001-067-TAP

density of storage cells 130 in a particular library, the camera vision system 360 of the present invention is implemented as a barcode laser scanner rather than a line scan camera as was typical in the prior art. Barcode
5 scanners are commonly available products used in systems, such as, for example, check out scanners for super markets and are well known in the art. A barcode scanner is smaller than a line scan camera. Therefore, less space is needed to accommodate the barcode scanner.

10 Thus, more room is available for storage cells, thereby increasing the storage density of a storage library.

With reference now to **Figure 6**, a diagram of a barcode scanning apparatus suitable for use with a cartridge retrieval system is depicted in accordance with
15 the present invention. Barcode scan apparatus 602 may be implemented as the camera vision system 360 in **Figure 3**. Barcode scan apparatus 602 includes a barcode laser or charge coupled device (CCD) scan engine 604, and an aperture 606. Barcode scan apparatus 602 is smaller than
20 the line scan camera used in the prior art. Therefore, a smaller amount of space is necessary to accommodate the camera vision system 360. Thus, more space in the library storage system may be devoted to storage cells, thereby increasing the storage density of the library
25 storage system.

Barcode scan cameras or engines have not been used for calibration purposes in the prior art because the output from barcode scanners is merely the decoded value of the bar code scanned by the barcode scanner.
30 Therefore, barcode scanners do not provide any pixel

Docket No. 2001-067-TAP

data. Furthermore, the scan width of the laser scanner beam from the barcode laser scanner is not controlled. Therefore, the proper calibration measurements cannot be made. However, to overcome these shortcomings, the

5 present invention incorporates an aperture 606 between the barcode scan engine 604 and a target barcode 608. The aperture opening 610 must be smaller than the scan width of the barcode scan engine 604, thus ensuring that the scan width 612 is uniform. The flexure is a

10 mechanical apparatus within the barcode scan engine that controls the movement of the mirror that reflects the laser light across an area. Since the flexure is mechanical, the movement of the robotic arm 110 during the calibration procedure will affect the flexure

15 causing the scan width 612 to be variable. The aperture 608 is situated to reduce the scan width generated by the movement of the flexure such that the scan width is uniform. This produces a non-variable scan-width giving a controlled end of scan.

20 To determine the center of the target in the direction parallel to the scan path, the robotic arm 110 is moved in the direction of scan path until the target 608 first becomes readable. This position is recorded through the use of a positional encoding device. The

25 robotic arm 110 continues to move in the same direction until the target is no longer readable by the barcode scanner apparatus 602. This position is also recorded. The center of the target in the scan path direction is then the half distance position between these two

30 positions.